

MD-320W

Ultrasound Biomicroscope for Ophthalmology

Description

- High frequency, high resolution
- B mode
- Two view ports (6.7mm × 5.3mm & 13.5mm × 10.6mm), full or half sulcus-to-sulcus images
- Flexible probe operation
- Alarm and Auto-Freezing when probe is blocked or approaches the cornea
- One clinical report can be accompanied with up to 30 images print out
- Image processing and measurement; reports storage, search and statistic
- Built-in calendar & clock




MD-320W Ultrasound Biomicroscope for Ophthalmology

SPECIFICATIONS

- Probe frequency: 50MHz
- Resolution: axial≤0.05mm, lateral≤0.1mm
- View ports: 6.7 mm x 5.3 mm, 13.5mm x 10.6 mm
- Display: 13.5°/27°
- Variable delay depth: 3~18 mm, adjustable by step of 1 mm
- Image processing: brightness, contrast, annotation, etc.
- Screen measurement: distance, angle, area, etc
- Report printable with: patient's information, clinical test, description of images
- Total gain: ≥105dBGray scale: 256 levelsFile formats: jpg, bmp













Room D,F3,Building C2, Xinmao Science Skill Park, Huayuan Industry Dev. Area, Tianjin 300384, China Phone: +86-22-83713881 Fax: +86-22-83713880 Website: www.MEDA.com.cn

E-mail: export@meda.com.cn